

# Singletons Peanut Butter Mill

## Specifications

<b><u>Dimensions:</u></b>	375mm (H) x 280mm (W) x 483mm (L) - (without acrylic hopper chute) 690mm (H) x 280mm (W) x 483mm (L) - (with acrylic hopper chute)
<b><u>Weight:</u></b>	32Kg Nett
<b><u>Electrical Motor:</u></b>	0.75kW, 4P, IP55, TEFC, 230VAC, 50HZ induction motor
<b><u>Voltage:</u></b>	230 V single-phase
<b><u>Current:</u></b>	6.5A
<b><u>Switch:</u></b>	DPST, 16A, 250VAC, IP44, Illuminated Rocker Switch
<b><u>Time Meter:</u></b>	8-digit, IP65, 264VAC time meter
<b><u>Production Capacity:</u></b>	50Kg of butter-stock peanuts ground per hour (feedstock size dependant)
<b><u>Hopper Capacity:</u></b>	7Kg of peanuts (incl. acrylic hopper chute)
<b><u>Duty Cycle:</u></b>	100%
<b><u>Warranty:</u></b>	Full one year manufacturer's warranty

- ✓ Proudly New Zealand made.
- ✓ Precision machined, durable, hygienic solid stainless steel grinder plates and feed screw for reliable operation and durability.
- ✓ Robust TEFC (totally enclosed fan cooled) motor for continuous duty cycle.
- ✓ Manual reset thermal overload protection of the motor.
- ✓ Calibrated time meter to reconcile stock usage.
- ✓ Ergonomically designed to be striking yet simple to use and clean.
- ✓ Can be supplied in most standard polyester powder-coat colours.
- ✓ Heavy duty 2.5m power cord.
- ✓ Manufacture to comply with AS/NZS 3820:2009 electrical safety standards.
- ✓ Electromagnetic Compatibility Compliance to AS/NZS CISPR 14.1:2010 (CISPR 14-1, Ed 5.1, 2009).
- ✓ Pictorial instruction manual and cleaning disassembly tools included.